

HUBBLE

LITHIUM BATTERY

ADVANCED ENERGY
STORAGE SYSTEMS



HUBBLE LITHIUM - AM-2 51V 5.5KW

- Advanced BMS with current limiting function
- CAN Bus, fully integrates and communicates with leading Inverter brands
- Excellent high temperature performance
- High Cycle Life and Service Life
- RIOT integration ready for cloud monitoring
- 1C High Performance Lithium battery
- High Energy Density and conversion efficiency
- Complete with integrated Battery Management System
- Compatible with most Inverters and chargers
- Low self discharge
- Easy wall mount or shelf rack installation
- Heavy duty side handles for easy handling and mounting on the wall
- Built in protection for over-charge, over-discharge & over-temperature



APPROVED BATTERY

ITEM	SPECIFICATION		
Model	Hubble AM-2		
Rated Capacity (5HR)	100 Ah		
Nominal Voltage	51.0 V		
Discharge Cutoff Voltage	42.0 V		
Equilized Charge Voltage	54.0 V		
Max. Continuous Charging Current	100 A		
Max. Continuous Discharging Current	100 A		
C Rating	1.0 C		
Weight	Approx. 42 Kg		
Display	None		
Parallel	Parallel connection up to 15 packs with full communications		
Dimensions (WxDxH) mm	375mm x 145mm x 467mm		
Ports	1x CAN-bus, 2x RS-485, 1x RS232		
Cells	New BYD Li-ion Cells		
Design Life	+/- 15 Years		
Cycle Life @ 1C	+/- 3 000 Cycles, afterwards 80% battery (retention) life left		
Certification	CE, UN38.3, GBT31484-2015, GBT31485-2015, GBT31486-2015		
Outer Package Material	White bake lacquer steel case		
Operating Temperature	Charging: 0 to +55°C	Discharging: -20 to +55°C	Storage: -20 to +55°C
Protection	Electronic Circuit Breaker, BMS Voltage Protection, Current Limiting		

* Due to continuous product improvements, specifications are subject to change without further notice.

All products are manufactured to the following standards:



**ADVANCED ENERGY
STORAGE SYSTEMS**

